

with label /  
mit Aufkleber



Ⓐ

**Mechanical characteristics**

interface dimensions acc. to assembly code  
mating life  
recommended coupling torque

**Components**

inner conductor  
cable lug  
screw  
other metal parts  
insulator  
gasket

**Electrical characteristics**

impedance  
frequency  
return loss  
insertion loss  
nominal DC spark-over voltage  
impulse discharge current (acc. to IEC 61643-21)

insulation resistance  
contact resistance  
center contact  
outer contact

**Environmental**

operating temp.  
protection class  
RoHS compliant

**Mechanische Eigenschaften**

Steckgesicht nach Montageanleitung  
Steckzyklen  
empfohlenes Kupplungsdrehmoment

**Bauteile**

Innenleiter  
Kabelschuh  
Schraube  
sonstige Metallteile  
Isolierung  
Dichtung

**Elektrische Eigenschaften**

Wellenwiderstand  
Frequenz  
Rückflussdämpfung  
Einfügedämpfung  
Nennansprechgleichspannung  
Stoßstromfestigkeit (nach IEC 61643-21)

Isolationswiderstand  
Durchgangswiderstand  
Innenkontakt  
Außenkontakt

**Umgebung**

Betriebstemperatur  
Schutzklasse  
RoHS konform

IEC 61169-66

E11  
≥100  
3 Nm

**Materials / Material**

CuBe2 / CuZn39Pb3  
Cu  
stainless steel/Edelstahl  
CuZn39Pb3  
PTFE / PS  
silicone/ Silikon


**Finish / Oberfläche**

Cu2Ag5  
Sn  
CuSnZn3

50 Ω  
0...3,8 GHz  
typ.: 30 dB@2,7 GHz; 20 dB@3,8 GHz  
typ.: 0,1 dB@2,7 GHz; 0,25 dB@3,8 GHz  
75 V  
10 x 15 kA (8/20µs)  
2 x 2,5 kA (10/350µs)  
300 x 200 A (10/1000µs)  
5 x 20 A (1s @ 50Hz)  
≥5 GΩ  
  
≤ 2 mΩ  
≤ 0,5 mΩ

-40°C / +85°C  
IP67 (IEC 60529)  
2011/65/EU

Änd./ rev. index	Änderungs-Nr. / revision code	Datum/ date	Name/ name	Datum/ date	Name/ name	Gewicht/ weight [g]
			gez./ drawn	10.09.2019	PU	
			gepr./ appr.	18.09.2019	BJ	ca./approx. 173
Maßstab/ scale		Benennung/ title				
1:1		2.2-5 SurSupG38 m-f 75V				
		2.2-5 SurSupG38 m-f 75V				
a	31770	17.11.2020	PU			
b	500000000279	25.01.2022	SKH			
untst. Maße/ dim. without tolerances according to		Untert./ doc. type		Materialnr./ material no.		
CUG		100025541				
Ersatz für/ replaces		PDM Nr./ pdm no.		J01465A0011		
				Maße/ dimensions: mm		
				Original : DIN A4		
				Blatt/ sheet 1 von/ of 1		



Maße/ dimensions: mm